Application No.: 10/711,943 Docket No.: 22171-00026-US1

AMENDMENTS TO THE CLAIMS

This Listing of Claims will replace all prior versions and listings of claims in this application.

Listing of Claims:

1. (Currently amended) A recording method for an optical disk drive, comprising the steps of:

detecting <u>during recording</u> at least one unstable signal source of the optical disk drive <u>and</u> <u>generating a detected value</u>, wherein the unstable signal source is selected from a group including a level of a focusing error signal, a level of a tracking error signal and a frequency of buffer under-run occurrence <u>during recording</u>;

ceasing recording if the detected value exceeds a preset threshold value;

decreasing a rotation speed of the optical disk drive; and

resuming recording with the decreased rotation speed.

- 2. (Original) The recording method for an optical disk drive in accordance with Claim 1, further comprising the step of detecting whether the optical disk drive is recording before the unstable signal source is detected.
- 3. (Original) The recording method for an optical disk drive in accordance with Claim 1, further comprising the step of ensuring that the recording is ceased after the operation of stopping recording is instructed.
- 4. (Original) The recording method for an optical disk drive in accordance with Claim 1, wherein ceasing recording and decreasing the rotation speed of the optical disk drive are controlled by a microprocessor.
- 5. (Previously Presented) A recording apparatus for an optical disk drive, comprising:

a driver for controlling a rotation speed of the optical disk drive;

Application No.: 10/711,943 Docket No.: 22171-00026-US1

a servo signal generation unit for generating a level of a focusing error signal, and a level of a tracking error signal during recording;

a microprocessor, comprising:

a detection mechanism for detecting an error rate of demodulating a frequency of buffer under-run occurrence;

a recording termination control mechanism for ceasing recording if an output of the detection mechanism or the servo signal generation unit exceeds a preset threshold value and the recording is underway; and

a recording speed adjustment mechanism for setting parameters with a lower rotation speed if the output of the detection mechanism or the servo signal generation unit exceeds a preset threshold value and the recording is ceased by the recording termination control mechanism; and

a digital signal processor for converting the parameters with the lower rotation speed into a driving signal that instructs the driver to decrease the rotation speed of the optical disk drive.

6. (Previously Presented) The recording apparatus for an optical disk drive in accordance with Claim 5, wherein the servo signal generation unit comprises:

a signal generator connected to an optical pickup head of the optical disk drive for generating the focusing error signal and the tracking error signal; and

a level detector for detecting the levels of the focusing error signal and the tracking error signal.

- 7. (Original) The recording apparatus for an optical disk drive in accordance with Claim 5, further comprising an encoder connected to the microprocessor.
- 8. (Original) The recording apparatus for an optical disk drive in accordance with Claim 7, further comprising a buffer connected to the encoder.
- 9. (Original) The recording apparatus for an optical disk drive in accordance with Claim 5, wherein if the output of the detection mechanism or the servo signal generation unit

Application No.: 10/711,943 Docket No.: 22171-00026-US1

exceeds a preset value and the recording is ceased, the recording termination control mechanism remains at the ceased status.